




2024

Ultra Series Catalog



A Station: ØD 1-12.7mm (1/2 "~1/2")

B Station: ØD 12.71-31.7mm (1/2"~1-1/4")

Stripper Plate

 \bigcirc

Open Guide


 \bigcirc

 \cap

PRODUCT OVERVIEW

The KU series is one of our's best-selling product lines, prized for its ease of use, reliability, and popularity. All categories are available in stations A, B, C, D and E, offering other mainstream tooling manufactures.

KU Series Parts Comparison Chart • Tool-free punch length adjustment is achieved by pushing the click release button and rotating Punch Head Punch Die the punch head clockwise or counterclockwise. Assembly Assemb \bigcirc \bigcirc \bigcirc • Max grind life for A & B station is 6.3mm. • Using HRC 63 High-Speed Steel for exceptional durability in high-stress environments. Guides treated with Nitriding process to enhance • compressive, wear, and corrosion resistance. TiCN coating available upon request for additional protection. • Interchangeable with other mainstream tooling manufacturers.



DealTech SOLUTIONS

Ultra Series

C/D/E Station

DESCRIPTION

Mate offers a wide range of C, D and E Station tooling systems to fit virtually any punching application.



ULTRA

- 0.212(5.38) more punch grind life than Original Style
 - Quick change strippers
- Quick length adjustment
- Internal lubrication within punch guide
- External lubrication between guide and turret bore ens uniform distribution of oil within the turret bore
- Hardened guides to reduce turret bore wear
- Slug Free dies eliminate slug pulling

URIGINAL STYLE PUNCHES

Mate Original Style punches are fully OEM compatibale. Made from premium high speed tool steel for optimal wear resistance, the punches include a 1/4 degree back taper and near polished flarks to reduce friction and eliminate galling.




C Station: ØD 31.71-50.80mm (1-1/4"~2") E Station: ØD 88.91-114.30mm (3-1/2"~4-1/2") D Station: ØD 50.81-88.90mm (2"~3-1/2")

PRODUCT OVERVIEW


The KU series is one of our's best-selling product lines, prized for its ease of use, reliability, and popularity. All categories are available in stations A, B, C, D and E, offering other mainstream tooling manufactures.

KU Series Parts Comparison Chart							
Parts Series	Punch Assembly	Punch Head Assembly	Punch	Die	Guide	Guide Assembly	Stripper Plate
KU	\bigcirc	0	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc

- Tool-free punch length adjustment is achieved by pressing the quick adjust button and rotating the punch head clockwise or counterclockwise.
- Max grind life for C, D, E station is about 8mm
- Using HRC 63 High-Speed Steel for exceptional durability in high-stress environments.
- TiCN coating available upon request for additional protection.
- Rooftop shear available upon request.
- Comes in 3 standard guiding pin angles of 0 90, 225.
- Interchangeable with other mainstream tooling manufacturers.







+39 0541-647041



info@dealtech.it sales@dealtech.it



Follow us



Viale Finale ligure,15 Riccione (RN)-47838 Italy-IT